

BS 1363 (UK) Surge & RFI Protected Adaptors



PD Devices BS1363 surge & RFI protected adaptor range is an ideal solution for home, office and industrial use.

The internal surge suppressors are tested against ‘worst case’ conditions, as defined in International Standards IEEE C62.41-1991 Cat B3 and comply with the recommendations of BS6651:1999 Annex C.

Specification:

Voltage Rating (Nominal)	230V rms
Maximum Current Rating	3A/7A/13A
Power Consumption	Negligible
Lead Length	2m
Surge Handling (8/20us) [Per Element]	19.5kA [6.5kA]
Average Attenuation, Symmetric 1-30MHz (dB)	-55 (3A)/-50 (7A)/-45 (13A)
Voltage Protection Level (Up) 8/20us	900V@3kA 8/20us
Response Time	<10ns
BS6651:1999 Annex C Location Category	A & B

Standard Features:


- Red status indicator to show mains power/fuse OK.

Options:

- Supplied in 3, 7, 10 or 13A versions.

PD Devices Ltd. Old Station Yard, South
 Brent, Devon. TQ10 9AL.
 T: +44 (0)1364 649248
 F: +44 (0)1364 649250
 E: contact@pddevices.co.uk

Order Codes:



Example – 7A rated Surge & RFI protected adaptor – Part Code: FA7

If you cannot see the socket configuration or additional features that you need, please call our customer service department on +44 (0)1364 649248 to discuss your requirements.

PD Devices Ltd. Old Station Yard, South
Brent, Devon. TQ10 9AL.
T: +44 (0)1364 649248
F: +44 (0)1364 649250
E: contact@pddevices.co.uk